SANG

P-Series IP Phones Powerful, feature-rich Desk Phones for Sangoma's suite of Communication Solutions

Sangoma's line of P-Series phones are designed to deliver the features you need, at price points perfect for every type of user, and every type of business. All models include color screens, high definition voice, are headset-ready, provide unprecedented plug-and-play deployment, and have built-in productivity applications including voicemail, call log, contacts, phone status, user presence, parking and more.

Sangoma's P-Series phones are the only phones that are compatible across Sangoma's communications as a service portfolio, further enhancing their value.*









	•			Coming Soon!	
P-Series	P310 & P315 Value Models	P320, P325, P330 Mid-Range Models	P370 Executive Model	PM200 Expansion Module	
Display	2.4" 320x240, Color	4.3" 480x272, Color, IPS	7.0" 1280x800, Color, IPS, Touch	4.3" 480x272, Color, IPS	
Touchscreen	No	No	Yes	No	
SIP Accounts	2	P320: 4 P325: 6 P330: 12	16 (using soft-keys)	N/A	
Programmable Keys (for Speed Dial / BLF or more SIP accounts)	2	P320: 4 P325: 6 P330: 12	16 (using soft-keys)	2 rows of 10 keys	
Virtual Pages of additional functionality (using pagination key)	N/A	P320: N/A P325: 20 w/pagination key P330: 10 w/pagination key	Up to 20 features/favorites on screen, w/scrolling to 100 features/favorites	20 keys and 2 pages	
Ethernet LAN and PC Port	P310: 100 Mbps P315: 1000 Mbps (Gigabit)	1000 Mbps (Gigabit)	1000 Mbps (Gigabit)	N/A	
Bluetooth and Built-in Wi-Fi (2.4/5G/802.11n)	No	P320 & P325: No P330: Yes	Yes	N/A	
Expansion Module Support	No	P320 & P325: No P330: Yes	Yes	Yes	

* some applications require server-side support that may vary between platforms

Learn more at www.sangoma.com/ip-phones/p-series

P-Series Phones

Phone Specifications

rore Executive-Level phone
User Interface
7.0 inch, 800 x 1280 pixel backlit color IPS LCD dis
Multi-point capacitive touch
 16 line appearances (software)
Feature and context-sensitive functions
Heauser, Speaker, Mute, and without backlight
Connections
• 2 switched 10/100/1000 whos Ethernet ports
• 12 volt 1.6A DC power port
• 2 Lock Ports
Dimensions/Weight
• 11" x 9.0" × 3.5", 2.7 os.
Software Minimum Version Requirements
 Switchvox >=79
 FreePBX & BXact >=15 with Endpoint Manager (la

P330, P325, and P320 Mid-Range phones **User Interface**

- 4.3 inch, 480 x 272 pixel backlit color IPS LCD display
- SIP Accounts
- P325 6
- e scroll key for virtual programmable keys:

indicator

Ethernet ports

- 6 feature keys 4 context-sensitive soft keys
- 6-key navigation controller and mute keys 2 volt 1.6A DC po
 - ng port
- oftware Minimum Version Requirements FreePBX & PBXact >=15 with Enclosint Manager (latest)

P310/P315 Value phones

User Interface

- 2.4 inch 320x240 pixel backlight color LCD display
- 2 line appearance keys
- · 4 feature keys
- · 4 context-sensitive soft keys
- · 6-key navigation controller
- Headset, speaker, and mute keys
- 3-color LED message waiting indicator
- Volume control

Connections

- 4P4C (RJ-9) handset/headset jack
- 2 switched 10/100 Mbps Ethernet ports (P310)
- 2 switched 10/100/1000 Mbps Ethernet ports (P315)
- 12 volt 1.6A DC power port
- 2 Lock ports
- Electronic Hookswitch signaling port

Dimensions/Weight

- 11.93" x 8.2" x 3.5", 2.4 lbs
- Software Minimum Version Requirements
- Switchvox >= 7.7
- FreePBX & PBXact >= 14 with Endpoint Manager (latest)

Operating Conditions

non-condensing

Warranty

One year

P310/P315 models

phone features

Storage Temperature

-4 to 160F / -20 to 70C

* Visual Voicemail not supported on

** Call Queues and Conferencing not

*** Some features are UC platform

SANG(*/N

p-series-phones-datasheet.20220622

specific; not all platforms support all

supported on all models

Temperature: +32 to 122F / 0 to 50C

• Relative Humidity: 5% to 95%

Series Specifications

Phone Applications****

- Visual Voicemail
- Contacts
- Presence/Status
- Call Log
- Parked Calls
- Call Queues **
- Info
- Forward Calls
- Conference App **
- Hot Desking ***

Phone Features

- Auto-Answer
- Headset-answer
- Headset-ring
- Distinctive ring
- Custom ringtones
- · Call waiting
- Call transfer (unattended & attended)

100 Renfrew Drive, Suite 100, Markham ON L3R 9R6 Canada 2 +1 (256) 428-6000 or 1 (877) 344 4861 (toll free in N. America)

- · Call forward
- Call hold
- Call parking Call pickup
- Intercom/Paging
- Message Waiting Indication
- Busy Lamp Field (BLF)
- 3-way conferencing
- Do Not Disturb (DND)
- Redial
- Call timer
- · Caller ID display

dio Feature

- · Handset, handsfree, and headset modes
- Full-duplex HD speakerphone with echo cancellation
- · Hearing aid compatible
- Multicast audio playback
- · Wideband: G.722
- · Narrowband: G.711 ulaw/alaw, G.726, G.729a

Network Support

- Static or DHCP IP address assignment
- NTP time synchronization
- · Priority queuing
- VLAN, LLDP, NAT traversal, QoS
- 802.1X pass-through
- 802.1X authentication

Language Support

• Dutch, English, French, German, Italian, Portuguese, Russian, Spanish

SIP / VoIP Support

- SIP v2
- TLS/SRTP
- DTMF, RFC4733
- · SIP peer-to-peer

Sangoma.com © 2022, Sangoma Technologies Inc. Sangoma Technologies is a registered trademark of Sangoma Technologies Corporation. Every effort has been made to ensure the accuracy of this document. However, Sangoma reserves the right to make changes without notice.

- SIP presence (SUBSCRIBE/NOTIFY) • Per-account digit map/dial plan
- Dial using SIP URI
- · Dial using SIP server
- Secure SIP authentication

Provisioning

- Business Voice & Business Voice + - Coming Late 2022
- Switchvox Cloud & Prem
- · Sangoma Endpoint Manager for
- PBXact and FreePBX DPMA (Deskphone Module for

· Firmware update via browser

· Remote logging via syslog

Regulatory Compliance

Maximum Power Consumption

• P320/P325 4.5W, 9.5W with USB

• P330: 8.2W, 5W per USB, 18.2W total

• P370: 8.5W, 5W per USB, 18.5W total

• FCC Part 15, Class B

- Asterisk) DHCP Option 66
- XML Configuration

Factory restore via UI

Management

CE Mark

• P310: 2.5W

• P315: 2.5W