ılıılıı cısco

Cisco IP Phone 7800 Series with Multiplatform Phone Firmware

This multiplatform phone firmware enables the 7800 Series to work with approved third-party call control systems.

Product Overview

For partners who provide voice and video services to end customers on third-party platforms, Cisco offers specific firmware loads that support these platforms and run on the Cisco[®] IP Phone 7800 Series. The feature set provided by this firmware is not identical to that of the firmware designed and built for use with Cisco call control systems, but there are many similarities. For clarity, this data sheet focuses only on the features provided on these multiplatform phone firmware loads. For a list of hardware-enabled functions, see the data sheets for the phones listed under the <u>Cisco IP Phone 7800 Series product information</u>.

This multiplatform phone firmware is offered exclusively on phones that are ordered with the SKUs listed in Table 4. Phones ordered as multiplatform phones do not work with Cisco call control. For any questions, reach out to <u>ipphone-pm-team alias</u>.

Supported Features

Table 1 lists the features supported in the multiplatform phone firmware.

Feature	Detail
Audio	 Codecs: G.711 (A-law and μ-law), G.722.2, G.722, G.729ab, ILBC, iSAC, OPUS DTMF: In-band, out-of-band (RFC 2833), and SIP INFO MOS Score Reporting (Telchemy)
Network	 MAC address (IEEE 802.3) SIP protocol support (RFC3261 and companion RFCs) IPv4 (RFC 791) IPv6 (RFC 2460): System Interoperability Testing Required DNS: A record (RFC 1706), SRV record (RFC 2782) Dynamic Host Configuration Protocol (DHCP) (RFC 2131) Simple Network Time Protocol (SNTP) (RFC 2030) Network Address Translation (NAT) transversal, serial tunnel (STUN) UDP/TCP Link Layer Discovery Protocol (LLDP) Cisco Discovery Protocol TR.69 Provisioning: System Interoperability Testing Required
Security	 802.1X authentication Media encryption via Secure Real-Time Transport Protocol (SRTP) Transport Layer Security (TLS) Encrypted configuration files Digest authentication Password login HTTPs secure provisioning Mandatory/Optional Secure call

Table I. Subbolled Feature	Table 1.	Supported Features
----------------------------	----------	--------------------

Feature	Detail
Applications	Cisco XML Services Interface (XSI) UC-One Presence
Call control and audio features	 Busy Lamp Field (BLF)¹ Call blocking – anonymous and selective Call conferencing – hosted (N-party)¹ Call conferencing – local 3-way Call forwarding – unconditional, no answer, on busy Call forwarding – unconditional, no answer, on busy Call park and unpark¹ Call park and unpark¹ Call transfer – attended or blind Call rol mame and number and outbound caller ID blocking Caller ID name and number and outbound caller ID blocking Caller ID name and number and outbound caller ID blocking Caller ID name and number and outbound caller ID blocking Caller ID name and number and outbound caller ID blocking Caller ID name and number and outbound caller ID blocking Caller ID name and number and outbound caller ID blocking Caller ID name and number and outbound caller ID blocking Caller ID name and number and outbound caller ID blocking Caller ID name and number and outbound caller ID blocking Caller ID name and number and outbound caller ID blocking Caller ID name and number and outbound caller ID blocking Configurable dial/numbering plan support with inter-digit timers – per line Configurable supplementary services soft keys Distinctive ringing based on calling and called number Do not disturb Extension mobility/hot-desking¹ Group paging¹ Hoteling¹ Intercom¹ Individual volume setting per audio path (headset/handset/speaker) Multicast paging Music on hold¹ Outbound caller ID blocking Visual Voice Message Waiting Indicator (VMWI) Shared/bridge line appearance¹ Supplementary services feature activation codes
Directory	 Local phonebook XML/LDAP remote directory Broadsoft directory Intelligent search Call history Reverse address lookup in all directories Intelligent Proximity (Mobile Contacts Synchronization)
Management	 Configuration: Browser/phone/auto-provision Auto-provision via TFTP/HTTP/HTTPs for mass deployment Packet Capture, Problem Reporting Tool (PRT), and upload of PRT

¹ Feature requires support by SIP client management server.

Platform Support

Table 2 lists the platforms supported by the multiplatform phone firmware.

Table 2.Supported Platforms

Platforms Supported	Certifications
Asterisk	Interoperability Tested – Release (1.8+)
Broadcloud	Interoperability Tested and Certified
Broadsoft Broadworks	Interoperability Tested and Certified – Releases 19sp1, 20sp1, 21sp1, 22sp1
Centile	Interoperability Tested and Certified – Release Istra SP 9.2
Metaswitch	Interoperability Tested and Certified – Release 9.3

Session Border Controller Support

Table 3 lists the session border controllers supported by the multiplatform phone firmware.

Session Border Controllers	
EdgeMarc	
Metaswitch Perimeter	
Oracle/Acme	
Sonus 5100	

Licensing

All Cisco IP Phone 7800 Series are covered by the Cisco End User License Agreement at https://www.cisco.com/go/eula.

Product Specifications

Table 4 lists the specifications for the multiplatform phone firmware. For more hardware specifications, see the <u>Cisco IP Phone 7800 Series data sheets.</u>

Table 4. Specifications

Feature	Details
Protocol support	SIP: all models
Full DN lines supported	7811: 1 line (SIP registration) 7821: 2 lines (SIP registrations) 7832: 1 line (SIP registration) 7841: 4 lines (SIP registrations) 7861: 16 lines (SIP registrations)
Language support	 Bulgarian Chinese (Simplified) Chinese (Traditional, Hong Kong) Croatian Czech Danish Dutch English (American) English (United Kingdom) Finnish

Feature	Details
	French (France)
	• German
	• Hungarian
	• Italian
	• Japanese
	• Korean
	Norwegian
	• Polish
	Portuguese (Portugal)
	Spanish (Spain)
	• Slovak
	• Swedish
	Slovenian
	• Turkish

Ordering Information

Table 5 provides information for ordering the 7800 Series phones with the multiplatform phone firmware.

Table 5.	Ordering Information
----------	----------------------

Part #	Product Description	
CP-7811-3PCC-K9=	Cisco IP Phone 7811 shipped with multiplatform phone firmware	
CP-7821-3PCC-K9=	Cisco IP Phone 7821 shipped with multiplatform phone firmware	
CP-7832-3PCC-K9=	Cisco IP Conference Phone 7832 shipped with multiplatform phone firmware	
CP-7841-3PCC-K9=	Cisco IP Phone 7841 shipped with multiplatform phone firmware	
CP-7861-3PCC-K9=	Cisco IP Phone 7861 shipped with multiplatform phone firmware	
Part Numbers for Remote Notes:	e Configuration:	
	p orders only. These part numbers are not available from Tier-2 distribution warehouse stocking inventory. roduct ID's support Remote Configuration (RC). It is no longer necessary to order specific "RC" SKUs to use the RC	
CP-7811-3PC-RC-K9=	Cisco IP Phone 7811 shipped with multiplatform phone firmware, for remote configuration	
CP-7821-3PC-RC-K9=	Cisco IP Phone 7821 shipped with multiplatform phone firmware, for remote configuration	
CP-7832-3PC-RC-K9=	Cisco IP Conference Phone 7832 shipped with multiplatform phone firmware, for remote configuration (Sept. 2017)	
CP-7841-3PC-RC-K9=	Cisco IP Phone 7841 shipped with multiplatform phone firmware, for remote configuration	
CP-7861-3PC-RC-K9=	Cisco IP Phone 7861 shipped with multiplatform phone firmware, for remote configuration	
Part Numbers for gift boxes that contain the phone along with the Power Cube and Cord: Notes: • Available the USA and Canada only.		
CP-7811-3PW-NA-K9=	Cisco IP Phone 7811 shipped with multiplatform phone firmware, and with a Power Cube and a power cord for North America	
CP-7821-3PW-NA-K9=	Cisco IP Phone 7821 shipped with multiplatform phone firmware, and with a Power Cube and a power cord for North America	
CP-7832-3PW-NA-K9=	Cisco IP Conference Phone 7832 shipped with multiplatform phone firmware, and with a Power Splitter, a Power Cube and a power cord for North America (December 2017)	
CP-7841-3PW-NA-K9=	Cisco IP Phone 7841 shipped with multiplatform phone firmware, and with a Power Cube and a power cord for North America	
CP-7861-3PW-NA-K9=	Cisco IP Phone 7861 shipped with multiplatform phone firmware, and with a Power Cube and a power cord for North America	

Warranty Information

The Cisco IP Phone 7800 Series is covered by the Cisco one-year limited hardware warranty.

Cisco Capital

Financing to Help You Achieve Your Objectives

Cisco Capital[®] can help you acquire the technology you need to achieve your objectives and stay competitive. We can help you reduce CapEx. Accelerate your growth. Optimize your investment dollars and ROI. Cisco Capital financing gives you flexibility in acquiring hardware, software, services, and complementary third-party equipment. And there's just one predictable payment. Cisco Capital is available in more than 100 countries. Learn more.

Call to Action

For more information about Cisco IP phone 7800 Series with Multiplatform Firmware, go to <u>https://www.cisco.com/go/mpp7800</u>.



Americas Headquarters Cisco Systems, Inc. San Jose, CA Asia Pacific Headquarters Cisco Systems (USA) Pte. Ltd. Singapore Europe Headquarters Cisco Systems International BV Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at https://www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: https://www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Printed in USA