



Compatible: Sangoma D-Series and S-Series IP Phones



For Desk IP Phones and Softphones

H20 Headset

Compatible:

Sangoma D-Series and S-Series IP Phones and Switchvox Softphone and Zulu (PBXact/FreePBX) softphone

Optimized for Sangoma IP desk phones and softphones.

Hands-Free Productivity

Give workers the freedom to roam around the office while staying connected to their phone calls with wireless ranges up to 325 feet. Answer phone calls directly from your wireless headset (using our optional EHS adaptors).

Superior sound Quality

DECT technology eliminates Wi-Fi interference and wideband audio provides crystal clear conversations.

Noise Cancellation

Eliminates background noises so that all callers are always heard.

Superior Call Handling

One-touch control with optional electronic hook switch adapters for call pickup, volume and mute up to 325 feet away from your desk for the ultimate flexibility.

All-Day Battery Life

Workers who answer calls all day, such as call center agents, can work comfortably with their headset always on, without worrying about battery.

On-call LED

Know when someone is on a call with on-call LED indication, and avoid interrupting their conversation.

H10

Designed for Sangoma D-Series and S-Series IP phones



H20

PC support adds softphone functionality over the H10



Designed with Automatic Configuration for Sangoma D/S-Series IP Phones and Softphones

H10 Specific:

Compatible Desk Phones:

- » S206, S305, S406, S505, S705
- » D60, D62, D65, D80

Visual Indicator:

» LED indicates call status, pairing status and other events

Desk Phone Connections:

» RJ-11 for handset, RJ-11 for phone body (or headset port), RJ-45 for EHS AUX

H20 Specific:

Compatible Desk Phones:

- » S206, S305, S406, S505, S705
- » D60, D62, D65, D80

Compatible Softphones:

- » Switchvox Desktop Softphone
- » FreePBX/PBXact: Zulu UC

Visual Indicator:

- » LED indicates call status, pairing status and other events
- » PC or Desk phone LED to indicate the active connection type

Desk Phone Connections:

» RJ-11 for handset, RJ-11 for phone body (or headset port), RJ-45 for EHS AUX

PC Connections:

Standard USB cable to PC with micro-USB connector on H20 Cradle

Toggle Mode:

Toggle button to switch between PC and Desk Phone mode

Common for H10 and H20:

Call Control:

Multi-function button support to answer, end, or reject calls

Volume Control and Microphone Mute:

» Button controls on headset

Microphone:

» Noise-canceling wideband microphone

Speaker(s):

» Wideband speaker

Range:

For U.S. DECT, up to 350 feet from H10 DECT Headset base to headset. For European DECT, up to 120 meters from H10 DECT Headset base to headset

Wireless Standard:

» (CAT - IQ) U.S. DECT and European DECT

Frequencies:

» U.S. DECT: 1.92 - 1.93 GHz. EU DECT: 1.88 -1.90 GHz

Sound Quality:

» DSP noise reduction; echo cancellation; tone control; wideband and narrowband audio

Audio Indicator:

Tones indicate incoming calls, low battery, volume level, microphone muting and other events

Wearing Style:

- » Headband and ear hook
- Long boom arm

Battery Type:

» Lithium Ion-Polymer

Battery Capacity:

» A300 mAh, typical

Battery Talk Time:

» Up to eight hours

Battery Standby Time:

» At least 36 hours

Battery Charge Time:

- >> 20% charge in less than 20 minutes
- > 50% charge in less than 45 minutes
- » Full charge in less than three hours

Battery Lifetime:

» Minimum 1000 charge cycles

Battery Shelf Life:

Headset battery holds charge for six months in the off state before recharge is required

Dialtone Adjustment Switch and Microphone Volume Switch:

» Electromechanical switches. Dialtone adjustment switch and microphone volume level set manually

Dimensions:

» 97 mm x 75 mm x 120 mm

Operating Environment:

> -0°C to +40°C; Up to 95% Rh non-condensing

Limited Warrenty:

» One year

Optional Accessories:

Electronic Hook Switch (EHS)

EHS adds* remote answer/disconnect convenience

*not required if using H20 with PC connection only since the softphones have this built-in functionality

» EHS ADAPTER

» Compatible with S406,S505,S705 (SKU:PHON-ACCS-EHS30-SNG)

» EHS CABLE

» Compatible with D60,D62,D65,D80 (SKU:1TELHC01LF)

